

Product Data Sheet



B-POEV 100K-SB

EAN 4047526622770

ID 622779

Pressed steel fixed castor, medium duty brackets, with top plate fitting, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centre, non-marking

Bracket:

Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

Tread colours: blue

Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Vulcanised tyre.

Wheel centre colour: black

Variant: non-marking



Rolling resistance

■■■■■□ Very good

Operating noise

■■■■■□ Very good

Floor surface preservation

■■■■■□ Very good

Product Data Sheet



Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		100 mm (D)
Wheel width		38 mm (T2)
Load capacity		200 kg
Total height		125 mm (H)
unit weight		0,6 kg
Temperature resistance		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

