



逆變式直流電弧焊機

ZX7 Inversion DC Arc Welder

ZX7系列



ZX7-500



ZX7-500I



ZX7-630I

技術參數 TECHNICAL DATA

型號 Model	ZX7-315	ZX7-315A	ZX7-400	ZX7-500	ZX7-500I	ZX7-630I
數據 Database						
輸入電源電壓頻率 Voltage Frequency of Input Power	AC380V ± 15% 50/60HZ	AC380V ± 15% 50/60HZ	AC380V ± 15% 50/60HZ	AC380V ± 15% 50/60HZ	AC380V ± 15% 50/60HZ	AC380V ± 15% 50/60HZ
額定輸入容量 KVA Rated Input Capacity	12.8	12.8	18	25	25	25
空載電壓 V Unloaded voltage	70	70	75	75	75	75
輸出電流調節範圍A Range of Output Current	20-315	20-315	20-400	20-500	40-500	40-500
額定輸出電壓 V Rated output voltage	33	33	36	40	40	40
負載持續率 % Load Endurance Rate	60	60	60	60	60	60
空載損耗 W Unloaded Consumption	80	80	100	100	200	200
效率 % Efficiency	85	85	85	85	85	85
功率因數 η Power Factor	0.93	0.93	0.93	0.93	0.93	0.93
絕緣等級 Insulation Class	B	B	B	B	B	B
重量 KG Weight	22	22	28	35	60	60
包裝尺寸 mm Packing Size	555X415X350	585X320X410	685X445X530	685X445X530	780X425X580	780X425X580
外殼防護等級 Cover Protected Level	IP21	IP21	IP21	IP21	IP21	IP21
推力調節範圍 A Drive Adjustment Range	0-100	0-100	0-100	0-100	0-100	0-100
適用焊條直徑 mm Electrode Diameter	2.5-5	2.5-5	2.5-6	2.5-6	2.5-6	2.5-6

