

# Product Data Sheet



## B-POEV 126K-SG

**EAN -**

**ID** 920315

**Pressed steel fixed castor with top plate fitting, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centre, non-marking**

**Bracket:**

Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

**Wheels:**

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

**Tread colours:** grey

**Wheel centre/rim:** Made of high-quality, impact-resistant nylon.

**Variant:** non-marking



**Rolling resistance**

■■■■□ Very good

**Operating noise**

■■■■□ Very good











**Floor surface preservation**

■■■■□ Very good

# Product Data Sheet



## Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		125 mm (D)
Wheel width		37 mm (T2)
Load capacity		150 kg
Total height		150 mm (H)
Bolt diameter		9 mm
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing