

Product Data Sheet



B-POEV 126K-SB

EAN -

ID 922168

Pressed steel rigid caster with top plate fitting, Heavy duty wheel with elastic solid rubber tires 'Blickle EasyRoll', with nylon wheel center, non-marking

Bracket:

Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel center.

Tread colours: blue

Wheel center/rim: Made of high-quality, impact-resistant nylon.

Variant: non-marking



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Very good











Floor surface preservation

■■■■□ Very good

Product Data Sheet



Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		125 mm (D)
Wheel width		37 mm (T2)
Load capacity		150 kg
Total height		150 mm (H)
Bolt diameter		9 mm
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tire hardness		65° Shore A
Bearing type		Ball bearing